#### **FABLOK®** 2x2 FABRIC **DISPLAY STAND**

- 4 x FABLOK® SEG Frame 1000mm (w)
- 1 x Arch Mounting Kit1 x 180° Linking Connector
- 2 x Half Feet Pair



**A)** Arch Mounting Kit (On Top) **x1** 



**B)** 180° Invisible Foot **x1** 




**C)** Half Feet Pair **x2** 








# FABLOK® SEG DISPLAY STAND

- 1. Unfold bottom frame section
- 2. Attach stabilising feet
- 3. Connect height extenders (2250mm (h) frames only)
- 4. Unfold top frame section
- 5. Add top frame to bottom frame section
- 6. Connect support pole(s)
- 7. Install silicone edge graphics























#### **FABLOK® CUPBOARD** KIT


- 1. Ensure all 1m wide frames are assembled, have graphics installed and stabilising feet removed
- 2. Add 90-degree bottom connectors on both rear corners
- 3. Add 90-degree top connectors on both rear corners
- Attach bottom door bar at the front of the cupboard
- 5. Mount access panel on hinge connectors
- Align the hinge connector when adding the top door bar
- Close the access panel to complete installation













FABLEK









## FABLOK® EXHIBITION ARCH INLINE MOUNTING

Assembly Instructions

- 1. Ensure all 1m (w) frames are assembled with graphics installed
- 2. Lay arch roof on the floor and remove stabilising feet
- 3. Organise the brackets for 'inline' mounting
- 4. Connect the brackets to each corner of the arch roof
- 5. Lift the arch roof into position to secure in place











FABLEK










## FABLOK® EXHIBITION ARCH ONTOP MOUNTING


- 1. Ensure all 1m (w) f rames are assembled with graphics installed
- 2. Lay arch roof on the floor and remove stabilising feet
- 3. Organise the brackets for 'ontop' mounting
- 4. Connect the brackets to each corner of the arch roof
- 5. Lift the arch roof into position to secure in place






















# FABLOK® 180 DEGREE CONNECTOR


- 1. Align two FABLOK® frames
- 2. Remove stabilising feet and add linking connector/foot
- 3. Add top connector to secure frames
- 4. Insert plastic clips to pinch two frames together























### FABLOK® T-CONNECTOR

- 1. Remove stabilising feet and align three FABLOK® frames in a T-configuration
- 2. Lift the frames one-by-one to mount the T-connector
- 3. Insert the top connector to secure the three frames











# FABLOK® 90 DEGREE CONNECTOR

- 1. Align two FABLOK® frames in a 90° configuration and remove stabilising feet
- 2. Lift the frames one-by-one to mount the bottom connector
- 3. Insert the top connector to secure frames
- 4. Mount the clear plastic clips top and bottom to secure the frames together

