FRONTIER MEDICAL SCREENS UREA RESISTANCE CERTIFICATE





Confidential Report

Our Ref: Supplement to E-005904/2



Notified Body for PPE Directive, Construction Products Regulation & Marine Equipment Directive I.D. No. 0338 & 0339



Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK.

Telephone: +44 (0) 161 876 4211 Email: <u>info@bttg.co.uk</u>

Date: 22 October 2018

Website: www.bttg.co.uk

Our Ref: Supplement to

Your Ref:

E-005904/2

Page: 1 of 5

Client: Camira Fabrics Limited

Meltham Mills Meltham West Yorkshire HD9 4AY

Job Title: Tests on one fabric

Client's Order No: 83A00933

Date of Receipt: 5th October 2018
Date of Test Start: 11th October 2018

Description of Sample(s): One fabric identified as follows, were received for testing:

Vita (C) Americano CALL 8348

Work Requested: We were asked to make the following tests:

Schildknecht Flexing ISO 7854: 1997 Method B

Determination of Sulphur Staining BS 3424 Method 22A





Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

> Email: <u>info@bttg.co.uk</u> Website: www.bttg.co.uk

Date: 22 October 2018

Our Ref: Supplement to

E-005904/2 Your Ref: --

2 of 4

Page:

Camira Fabrics Limited

Samples were identified as follows:

Vita (C) Americano CALL 8348

Laboratory Work

The tests were made in Standard Atmosphere (65 \pm 4% relative humidity at 20 \pm 2°C) the sample having been freely and continuously exposed to that atmosphere for at least 24 hours prior to testing. Specimens have been taken from the sample as described in the specified standard.

Resistance to Damage by Flexing

Flex cracking resistance was tested following the procedure in Method B – Schildknecht method, of BS EN ISO 7854: 1997 (BS 3424: Part 9: 1996), "Rubber- or plastics-coated fabrics – Determination of resistance to damage by flexing". Three specimens, in each direction, were tested for a predetermined number of cycles.

At the clients' request, the specimens were to be inspected at 400 000 cycles.

The flexing damage was assessed according to the following methods.

The overall appearance of the specimens was assessed for deterioration considering all visible factors such as wrinkling, cracking, flaking and discolouration. Specimens were graded, without magnification, using the 4 part numerical scale.

Each specimen was examined, under magnification, to determine depth, length and number of cracks. Depth of cracking was assessed using the descriptive scale. The length of the longest crack (mm) and the number of cracks have been reported.

Determination of Sulphur Staining

The sample was tested in accordance with Method 22A of BS 3424: Part 19: 1989 (2016).

Both surfaces of the test specimen were compared with the original sample and the contrast between them assessed using standard grey scales for staining; 5 represents no staining and 1 severe staining.

The results for all tests are given in the table on the following page.





Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

> Email: <u>info@bttg.co.uk</u> Website: <u>www.bttg.co.uk</u>

Date: 22 October 2018

Our Ref: Supplement to

E-005904/2 Your Ref: --

Page: 3 of 4

Camira Fabrics Limited

RESULTS

Sample Ref: Vita (C) Americano CALL 8348

ASSESSMENT OF SCHILDKNECHT FLEX DAMAGE AT 400 000 CYCLES										
Specimen Number	1 (Length)	2 (Length)	3 (Length)	4 (Width)	5 (Width)	6 (Width)				
Deterioration in Appearance	2-3	2-3	2-3	2-3	2-3	2-3				
Type of damage (if any)	Moderate to severe creasing									
Depth of Cracking	А	Α	Α	А	А	А				
Number of Cracks Of The Lowest Grade	> 10	6	6	1	1	3				
Length Of Longest Crack of The Lowest Grade (mm)	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5				

Deterioration In appearance		Dept	Depth of Cracking			
0	None	Nil	no cracking			
1	Slight	Α	surface or finish crack, not exposing the cellular or middle layer			
2	Moderate	В	cracking into but not right through the middle layer, or, in the case of single-layer coatings, not exposing the base fabric			
3	Severe	С	cracking through to the base fabric			
		D	cracking right through the material			





Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 22 October 2018

Our Ref: Supplement to

E-005904/2 Your Ref: --

Page: 4 of 4

Camira Fabrics Limited

RESULTS

Sample Ref: Vita (C) Americano CALL 8348

Determination of Sulphur Staining

	Face side	Reverse side
Staining rating immediately after test	4-5	4
Staining rating after 24 hours	4-5	4

Reported by: Miss E Goodfellow
Laboratory Technician

Countersigned by: Mr P Hutchings
Operational Head

Note: This report relates only to the samples submitted and as described in the report.

Enquiries concerning this report should be addressed to Customer Services.

